

SIMATIC S7-300, CPU 314C-2DP COMPACT CPU WITH MPI, 24 DI/16 DO, 4AI, 2AO, 1 PT100, 4 FAST COUNTERS (60 KHZ), INTEGRATED DP INTERFACE, INTEGRATED 24V DC POWER SUPPLY, 64 KBYTE WORKING MEMORY, FRONT CONNECTOR (X 40PIN) AND MICRO MEMORY CARD REQUIRED

General information	
Hardware product version	01
Firmware version	V2.0.0
Engineering with	
Programming package	STEP 7 V5.2 + SP1 or higher with HW update
Supply voltage	
Rated value (DC)	
24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Load voltage L+	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	1 000 mA
Current consumption (in no-load operation), typ.	150 mA
Inrush current, typ.	11 A
I^2t	0.7 A ² ·s
Power loss	
Power loss, typ.	14 W
Memory	
Work memory	
integrated	64 kbyte; For program and data
expandable	No
Load memory	
Plug-in (MMC)	Yes
Plug-in (MMC), max.	8 Mbyte
Data management on MMC (after last programming), min.	10 y
Backup	
present	Yes; Guaranteed by MMC (maintenance-free)

- without battery

Yes; Program and data

CPU processing times

for bit operations, typ.	0.1 µs
for word operations, typ.	0.2 µs
for fixed point arithmetic, typ.	2 µs
for floating point arithmetic, typ.	3 µs

CPU-blocks

Number of blocks (total)	1 024
DB	
• Number, max.	511; Number range: 1 to 511
• Size, max.	16 kbyte
FB	
• Number, max.	512; Number range: 0 to 2047
• Size, max.	16 kbyte
FC	
• Number, max.	512; Number range: 0 to 2047
• Size, max.	16 kbyte
OB	
• Number, max.	see instruction list
• Size, max.	16 kbyte
• Number of free cycle OBs	1; OB 1
• Number of time alarm OBs	1; OB 10
• Number of delay alarm OBs	1; OB 20
• Number of cyclic interrupt OBs	1; OB 35
• Number of process alarm OBs	1; OB 40
• Number of startup OBs	1; OB 100
• Number of asynchronous error OBs	1; OB 80
• Number of synchronous error OBs	2; OB 121, 122
Nesting depth	
• per priority class	8
• additional within an error OB	4

Counters, timers and their retentivity

S7 counter	
• Number	256
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	256
Counting range	
— lower limit	0
— upper limit	999

S7 times	
• Number	256
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	256
— preset	No retentivity
Time range	
— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
• present	Yes
• Type	SFB
Data areas and their retentivity	
retentive data area in total	all
Flag	
• Number, max.	256 byte
• Retentivity available	Yes; MB 0 to MB 255
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8
Data blocks	
• Number, max.	511
• Size, max.	16 kbyte
• Retentivity adjustable	No
• Retentivity preset	Yes
Local data	
• per priority class, max.	510 byte
Address area	
I/O address area	
• Inputs	1 kbyte
• Outputs	1 kbyte
Process image	
• Inputs	128 byte
• Outputs	128 byte
Default addresses of the integrated channels	
— Digital inputs	124.0 to 126.7
— Digital outputs	124.0 to 125.7
— Analog inputs	752 to 761
— Analog outputs	752 to 755
Digital channels	
• Inputs	992

— of which central	992
• Outputs	992
— of which central	992
Analog channels	
• Inputs	512
— of which central	248
• Outputs	124
— of which central	248
Hardware configuration	
Number of expansion units, max.	3
Number of DP masters	
• integrated	1
• via CP	4
Number of operable FMs and CPs (recommended)	
• FM	8
• CP, PtP	8
• CP, LAN	10
Rack	
• Racks, max.	4
• Modules per rack, max.	8; In rack 3 max. 7
Time of day	
Clock	
• Hardware clock (real-time)	Yes
• retentive and synchronizable	Yes
• Backup time	6 wk
• Deviation per day, max.	10 s
Operating hours counter	
• Number	1
• Number/Number range	0
• Range of values	0 to 2 ³¹ hours (when using SFC 101)
• Granularity	1 hour
• retentive	Yes
Clock synchronization	
• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes
• in AS, master	Yes
Digital inputs	
Number of digital inputs	24
integrated channels (DI)	24
Input voltage	

• Rated value (DC) • for signal "0" • for signal "1"	24 V -3 to +5V +15 to +30V
Input current	
• for signal "1", typ.	8 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.1 / 0.3 / 3 / 15 ms
for counter/technological functions	
— at "0" to "1", max.	8 µs
Cable length	
• shielded, max. • unshielded, max.	1 000 m; 100 m for technological functions 600 m
Digital outputs	
Number of digital outputs	16
integrated channels (DO)	16
Short-circuit protection	Yes; Clocked electronically
Limitation of inductive shutdown voltage to	L+ (-48 V)
Output voltage	
• for signal "1", min.	L+ (-0.8 V)
Output current	
• for signal "1" permissible range for 0 to 60 °C, max. • for signal "1" minimum load current • for signal "0" residual current, max.	500 mA 5 mA 0.5 mA
Switching frequency	
• with resistive load, max. • with inductive load, max.	100 Hz 0.5 Hz
Total current of the outputs (per group)	
all mounting positions	
— up to 40 °C, max.	8 A
— up to 60 °C, max.	4 A
Cable length	
• shielded, max. • unshielded, max.	1 000 m 600 m
Analog inputs	
Number of analog inputs	
• For voltage/current measurement • For resistance/resistance thermometer measurement	4 1
integrated channels (AI)	4+1

permissible input voltage for current input (destruction limit), max.	5 V; Permanent
permissible input current for voltage input (destruction limit), max.	0.5 mA; Permanent
Technical unit for temperature measurement adjustable	Yes; Degrees Celsius / degrees Fahrenheit / Kelvin
Input ranges	
• Current	Yes
• Resistance thermometer	Yes
• Resistance	Yes
Input ranges (rated values), voltages	
• 0 to +10 V	Yes
• Input resistance (0 to 10 V)	100 k Ω
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
• Input resistance (0 to 20 mA)	100 Ω
• -20 mA to +20 mA	Yes
• Input resistance (-20 mA to +20 mA)	100 Ω
• 4 mA to 20 mA	Yes
• Input resistance (4 mA to 20 mA)	100 Ω
Input ranges (rated values), resistance thermometer	
• Pt 100	Yes
• Input resistance (Pt 100)	10 M Ω
Input ranges (rated values), resistors	
• 0 to 600 ohms	Yes
• Input resistance (0 to 600 ohms)	10 M Ω
Cable length	
• shielded, max.	100 m
Analog outputs	
Number of analog outputs	2
integrated channels (AO)	2
Output ranges, voltage	
• 0 to 10 V	Yes
• -10 V to +10 V	Yes
Output ranges, current	
• 0 to 20 mA	Yes
• -20 mA to +20 mA	Yes
• 4 mA to 20 mA	Yes
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	12 bit

- Integration time, parameterizable

Yes; 2,5 / 16,6 / 20 ms

Analog value generation for the outputs

Integration and conversion time/resolution per channel

- | | |
|--|--------|
| • Resolution with overrange (bit including sign), max. | 12 bit |
| • Conversion time (per channel) | 1 ms |

Encoder

Connectable encoders

- | | |
|---|--------|
| • 2-wire sensor | Yes |
| — permissible quiescent current (2-wire sensor), max. | 1.5 mA |

Errors/accuracies

Basic error limit (operational limit at 25 °C)

- | | |
|--|-------|
| • Voltage, relative to input range, (+/-) | 0.7 % |
| • Current, relative to input range, (+/-) | 0.7 % |
| • Resistance, relative to input range, (+/-) | 3 % |
| • Resistance thermometer, relative to input range, (+/-) | 3 % |
| • Voltage, relative to output range, (+/-) | 0.7 % |
| • Current, relative to output range, (+/-) | 0.7 % |

Interfaces

MPI

- | | |
|----------------------|------------------------|
| • Cable length, max. | 50 m; without repeater |
|----------------------|------------------------|

1. Interface

Interface type	Integrated RS 485 interface
----------------	-----------------------------

Physics	RS 485
---------	--------

Isolated	No
----------	----

Power supply to interface (15 to 30 V DC), max.	200 mA
---	--------

Functionality

- | | |
|-----------------------------|-----|
| • MPI | Yes |
| • PROFIBUS DP master | No |
| • PROFIBUS DP slave | No |
| • Point-to-point connection | No |

MPI

- | | |
|---------------------------|--------------|
| • Number of connections | 12 |
| • Transmission rate, max. | 187.5 kbit/s |

Services

- | | |
|-----------------------------|-----|
| — PG/OP communication | Yes |
| — Routing | Yes |
| — Global data communication | Yes |

— S7 basic communication	Yes
— S7 communication	Yes
— S7 communication, as client	No
— S7 communication, as server	Yes

2. Interface

Interface type	Integrated RS 485 interface
Physics	RS 485
Isolated	Yes
Power supply to interface (15 to 30 V DC), max.	200 mA
Number of connection resources	12
Functionality	
• MPI	No
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
• Point-to-point connection	No
DP master	
• Number of connections, max.	12; For PG/OP communication
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	32
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	Yes
— S7 communication	Yes
— S7 communication, as client	No
— S7 communication, as server	Yes
— Equidistance	Yes
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	Yes
— DPV1	Yes
Address area	
— Inputs, max.	1 kbyte
— Outputs, max.	1 kbyte
User data per DP slave	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
DP slave	
• Number of connections	12

• GSD file	The latest GSD file is available at: http://www.ad.siemens.de/support in Product Support area
• Transmission rate, max.	12 kbit/s
• automatic baud rate search	Yes
• Address area, max.	32
• User data per address area, max.	32 byte
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	Yes
— S7 communication	Yes
— S7 communication, as client	No
— S7 communication, as server	Yes
— Direct data exchange (slave-to-slave communication)	Yes
— DPV1	No
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte
Communication functions	
PG/OP communication	Yes
Global data communication	
• supported	Yes
• Number of GD loops, max.	4
• Number of GD packets, max.	4
• Number of GD packets, transmitter, max.	4
• Number of GD packets, receiver, max.	4
• Size of GD packets, max.	22 byte
• Size of GD packet (of which consistent), max.	22 byte
S7 basic communication	
• supported	Yes
• User data per job, max.	76 byte
• User data per job (of which consistent), max.	76 byte
S7 communication	
• supported	Yes
• as server	Yes
• as client	Yes; Via CP and loadable FB
• User data per job, max.	180 kbyte
• User data per job (of which consistent), max.	64 byte
S5 compatible communication	

• supported	Yes; via CP and loadable FC
Number of connections	
• overall	12
• usable for PG communication	11
— reserved for PG communication	1
— adjustable for PG communication, min.	1
— adjustable for PG communication, max.	11
• usable for OP communication	11
— reserved for OP communication	1
— adjustable for OP communication, min.	1
— adjustable for OP communication, max.	11
• usable for S7 basic communication	8
— reserved for S7 basic communication	8
— adjustable for S7 basic communication, min.	0
— adjustable for S7 basic communication, max.	8
• usable for routing	4
S7 message functions	
Number of login stations for message functions, max.	12
Process diagnostic messages	Yes
simultaneously active Alarm-S blocks, max.	40
Test commissioning functions	
Status block	Yes
Single step	Yes
Number of breakpoints	2
Status/control	
• Status/control variable	Yes
• Variables	Inputs, outputs, memory bits, DB, times, counters
• Number of variables, max.	30
— of which status variables, max.	30
— of which control variables, max.	14
Forcing	
• Forcing	Yes
• Forcing, variables	Inputs, outputs
• Number of variables, max.	10
Diagnostic buffer	
• present	Yes
• Number of entries, max.	100
Integrated Functions	
Number of counters	4

Counting frequency (counter) max.	60 kHz
Frequency measurement	Yes
Number of frequency meters	4
controlled positioning	Yes
PID controller	Yes
Number of pulse outputs	4
Limit frequency (pulse)	2.5 kHz

Potential separation

Potential separation digital inputs

- | | |
|--|-----|
| • Potential separation digital inputs | Yes |
| • between the channels, in groups of | 16 |
| • between the channels and backplane bus | Yes |

Potential separation digital outputs

- | | |
|--|-----|
| • Potential separation digital outputs | Yes |
| • between the channels, in groups of | 8 |
| • between the channels and backplane bus | Yes |

Potential separation analog inputs

- | | |
|--|----------------------------|
| • Potential separation analog inputs | Yes; common for analog I/O |
| • between the channels and backplane bus | Yes |

Potential separation analog outputs

- | | |
|--|----------------------------|
| • Potential separation analog outputs | Yes; common for analog I/O |
| • between the channels and backplane bus | Yes |

Configuration

Configuration software

- | | |
|----------|------------------------------|
| • STEP 7 | Yes; V5.2 SP1 with HW update |
|----------|------------------------------|

Programming

- | | |
|--------------------------------|----------------------|
| • Command set | see instruction list |
| • Nesting levels | 8 |
| • System functions (SFC) | see instruction list |
| • System function blocks (SFB) | see instruction list |

Programming language

- | | |
|------------|-----|
| — LAD | Yes |
| — FBD | Yes |
| — STL | Yes |
| — SCL | Yes |
| — CFC | Yes |
| — GRAPH | Yes |
| — HiGraph® | Yes |

Know-how protection

- | | |
|---|-----|
| • User program protection/password protection | Yes |
|---|-----|

Dimensions

Width	120 mm
Height	125 mm
Depth	130 mm

Weights

Weight, approx.	676 g
-----------------	-------

last modified: 08/12/2017